

# HBTS60-13-90

## CONCRETE TRAILER PUMP

**SHANTUI**  
VALUE THAT WORKS

理论输送量Theoretical capacity	45/68 m <sup>3</sup> /h
泵送工作压力Hydraulic pressure	30 Mpa
料斗容积/上料高度Bucket capacity/Feeding height	0.5/1400 m <sup>3</sup> /mm

KEEP POWER & CARRY MORE



SHANTUI CONSTRUCTION MACHINERY CO., LTD.  
ADDRESS: No. 58, G327 Highway, Jining City, Shandong, CHINA  
TEL: +86-537-2909369 FAX: +86-537-2311219  
EMAIL: trade@shantui.com WEB: www.shantui.com



www.shantui.com

# HBTS60-13-90 TECHNICAL PARAMETERS

## CONCRETE TRAILER PUMP

**SHANTUI**  
VALUE THAT WORKS

项目ITEM	单位	HBTS60-13-90
理论输送量Theoretical capacity	m <sup>3</sup> /h	45/68
混凝土最大输送距离 (水平/垂直) Max. conveying distance (Horizontal/Vertical)	m	1200/270
泵送混凝土最大压力Max. pumping pressure	Mpa	13
分配阀型式Selector valve type		S管/Pipe
最大骨料粒径/Max. aggregate size	mm	碎石Gravel≤40, 卵石Pebble≤50
坍落度/Slump	mm	180~220
混凝土缸/Concrete cylinder	mm	φ200×1650
主油缸Master cylinder	mm	φ125×φ80×1650
料斗容积/上料高度Bucket capacity/Feeding height	m <sup>3</sup> /mm	0.5/1400
泵送工作压力Hydraulic pressure	Mpa	30
分配压力Distribution pressure	Mpa	16
料斗搅拌工作压力Bucket mixing work pressure	Mpa	14
液压油箱容积Hydraulic oil tank capacity	L	500
清洗方式Cleaning type		高压水洗/High pressure water spraying
电机Motor	kw	90
油泵Oil pump	ml/r	双112 (韩国川崎)South Korea kawasaki
阀组Valve bank		德国伯森/BOLSEEN
液压胶管Hydraulic rubber tube		意大利玛努力/ MANULI
电气Electrics		正泰(Chint)、施耐德(Schneider)、三菱(Mitsubishi)
输送管Delivery pump		φ125/150米M
外形尺寸 (长×宽×高) Overall dimension	mm	6480×2200×2300



\* THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.